



Engineered for transferring a variety of corrosive liquids. Robust Polypropylene ensures chemical resistance against light to aggressive chemicals.

## Technical Specifications

- Package Includes:**..... Motor, Pump Tube, Hose, Storage Bracket, Barrel Adapter & Hand Nozzle
- Motor Type:**..... 230V, 950 W, IP54, Variable Speed Drive
- Pump Tube Material:**.. Polypropylene, Hastelloy C-276, Carbon Graphite
- Immersion Length:**..... 39" (1000 mm) or 47" (1200 mm)
- Discharge Hose:** .....PVC, 1,8 m, 1" (25 mm) I.D.
- Hand Nozzle Material:** .....Polypropylene, Viton
- Maximum Flow Rate:**..... 67 L/min based on water
- Maximum Viscosity:**..... 1500 cps (mPas)
- Maximum Temperature:** ..... 55° C
- Shipping Weight:**.....9,97 kg



## DRUM & IBC tanks

Package P/N	Motor	Power	Pump Tube
9530	SPE-950V	950 W	SP-PP-39
9531	SPE-950V	950 W	SP-PP-47



**Warning: This pump is not suitable for use with Flammable/Combustible liquids.**

\*Note: When pumping viscosities over 1,000 cps, pump must be used intermittently to avoid potential premature failure and/or damage.